



**Program Directory for
IBM DB2 DataPropagator Q Capture
for VM**

Version 7 Release 4.0

Program Number 5697-F42

for Use with
z/VM

Document Date: September 2004

GI10-5000-02

Note!

Before using this information and the product it supports, be sure to read the general information under "Notices" on page iv.

This program directory, dated September 2004, applies to DataPropagator Q Capture for VM Version 7 Release 4.0 (DB2 DProp Q Capture for VM V7.4), Program Number 5697-F42.

A form for reader's comments appears at the back of this publication. When you send information to IBM, you grant IBM a nonexclusive right to use or distribute the information in any way it believes appropriate without incurring any obligation to you.

© **Copyright International Business Machines Corporation 1997, 2004. All rights reserved.**

US Government Users Restricted Rights – Use, duplication or disclosure restricted by GSA ADP Schedule Contract with IBM Corp.

Contents

Notices	iv
Trademarks and Service Marks	iv
1.0 Introduction	1
1.1 Program Description	1
2.0 Program Materials	3
2.1 Basic Machine-Readable Material	3
2.2 Optional Machine-Readable Material	4
2.3 Program Publications	4
2.3.1 Basic Program Publications	4
2.4 Microfiche Support	4
2.5 Publications Useful During Installation	5
3.0 Program Support	6
3.1 Preventive Service Planning	6
3.2 Statement of Support Procedures	6
4.0 Program and Service Level Information	7
4.1 Program Level Information	7
4.2 Service Level Information	7
4.3 Cumulative Service Tape	7
5.0 Installation Requirements and Considerations	8
5.1 Hardware Requirements	8
5.2 Program Considerations	8
5.2.1 Operating System Requirements	8
5.2.2 Other Program Product Requirements	8
5.2.3 Program Installation/Service Considerations	8
5.3 DASD Storage and user ID Requirements	9
6.0 Installation Instructions	11
6.1 VMSES/E Installation Process Overview	11
6.2 Plan Your Installation For DB2 DProp Q Capture for VM V7.4	12
6.3 Allocate Resources for Installing DB2 DProp Q Capture for VM V7.4	15
6.3.1 Installing DB2 DProp Q Capture for VM V7.4 on Minidisk	15
6.3.2 Installing DB2 DProp Q Capture for VM V7.4 in SFS Directories	17
6.4 Install DB2 DProp Q Capture for VM V7.4	19
6.4.1 Update Build Status Table for DB2 DProp Q Capture for VM V7.4	23
6.5 Place DB2 DProp Q Capture for VM V7.4 Into Production	23
6.5.1 Customize the CAPTMACH user ID	23
6.5.2 Copy DB2 DProp Q Capture for VM V7.4 Files Into Production	24

6.5.3 Load the DB2 DProp Q Capture for VM V7.4 Package files to a database	24
6.5.4 Starting DB2 DProp Q Capture for VM V7.4	25
6.5.5 Installation Verification Procedure for DB2 DProp Q Capture for VM V7.4	25
6.6 Post-Installation Considerations (optional)	26
7.0 Migration Instructions	27
8.0 Service Instructions	28
8.1 VMSES/E Service Process Overview	28
8.2 Servicing DB2 DProp Q Capture for VM V7.4	29
8.2.1 Prepare to Receive Service	29
8.2.2 Receive the Service	31
8.2.3 Apply the Service	31
8.2.4 Update the Build Status Table	32
8.2.5 Build Serviced Objects	34
8.3 Place the New DB2 DProp Q Capture for VM V7.4 Service Into Production	34
8.3.1 Copy the New DB2 DProp Q Capture for VM V7.4 Serviced Files Into Production	34
8.3.2 Load the DB2 DProp Q Capture for VM V7.4 Package files to a database	35
Reader's Comments	37

Figures

1. Basic Material: Program Tape	3
2. Program Tape: File Content	3
3. Basic Material: Unlicensed Publications	4
4. Publications Useful During Installation / Service on VM/ESA Version 4.3	5
5. PSP Upgrade and Subset ID	6
6. Component IDs	6
7. DASD Storage Requirements for Target Minidisks	9

Notices

References in this document to IBM products, programs, or services do not imply that IBM intends to make these available in all countries in which IBM operates. Any reference to an IBM product, program, or service is not intended to state or imply that only IBM's product, program, or service may be used. Any functionally equivalent product, program, or service that does not infringe on any of IBM's intellectual property rights may be used instead of the IBM product, program, or service. Evaluation and verification of operation in conjunction with other products, except those expressly designated by IBM, is the user's responsibility.

IBM may have patents or pending patent applications covering subject matter in this document. The furnishing of this document does not give you any license to these patents. You can send license inquiries, in writing, to the

International Business Machines Corporation
IBM Director of Licensing
North Castle Drive, Armonk, NY
10504-1785, U.S.A.

Trademarks and Service Marks

The following terms used in this document, are trademarks or service marks of IBM Corporation in the United States or other countries or both:

IBM
VM/ESA
z/VM
IBMLink(Service Link)
DATABASE 2
DB2 Server for VM

1.0 Introduction

This program directory is intended for the system programmer responsible for program installation and maintenance. It contains information concerning the material and procedures associated with the installation of DB2 DProp Q Capture for VM V7.4. You should read all of this program directory before installing the program and then keep it for future reference.

The program directory contains the following sections:

- 2.0, "Program Materials" on page 3 identifies the basic and optional program materials and documentation for DB2 DProp Q Capture for VM V7.4.
- 3.0, "Program Support" on page 6 describes the IBM support available for DB2 DProp Q Capture for VM V7.4.
- 4.0, "Program and Service Level Information" on page 7 lists the APARs (program level) and PTFs (service level) incorporated into DB2 DProp Q Capture for VM V7.4.
- 5.0, "Installation Requirements and Considerations" on page 8 identifies the resources and considerations for installing and using DB2 DProp Q Capture for VM V7.4.
- 6.0, "Installation Instructions" on page 11 provides detailed installation instructions for DB2 DProp Q Capture for VM V7.4.
- 8.0, "Service Instructions" on page 28 provides detailed servicing instructions for DB2 DProp Q Capture for VM V7.4.

Before installing DB2 DProp Q Capture for VM V7.4, read 3.1, "Preventive Service Planning" on page 6. This section tells you how to find any updates to the information and procedures in this program directory.

1.1 Program Description

DataPropagator Q Capture for VM is part of the IBM Replication solution. IBM Replication is a set of easy-to-use, automated copy tools that replicate relational data from sources to targets. You can use IBM Replication to define, synchronize, automate, and manage copy operations from a single control point for data across your enterprise. You can tailor or enhance data as it is copied and deliver detailed, subset, summarized, or derived data when and where it is needed.

IBM Replication consists of the following tools:

- Replication Center
Provides the graphical user interface (GUI) that you use for administration tasks. The Replication Center is part of DB2 Universal Database.
- Capture Program

Captures changes made to data in replication source tables by reading the database log. It places the captured changes into change data tables. It runs independently of the Replication Center, but uses control information created by it.

- **Apply Program**

Reads the changed data previously captured and stored in a change data table and applies the changes to target tables or reads data directly from source tables. Like the Capture program, it runs independently of the Replication Center, using control information created by it.

2.0 Program Materials

An IBM program is identified by a program number. The program number for DataPropagator Q Capture for VM Version 7 is 5697-F42.

The program announcement material describes the features supported by DB2 DProp Q Capture for VM V7.4. Ask your IBM marketing representative for this information if you have not already received a copy.

The following sections identify:

- basic and optional program materials available with this program
- publications useful during installation.

2.1 Basic Machine-Readable Material

The distribution medium for this program is 9-track magnetic tape (written at 6250 BPI), 3480 tape cartridge, 1/4-inch tape cartridge or 4mm tape cartridge. The tape or cartridge contains all the programs and data needed for installation. See section 6.0, "Installation Instructions" on page 11 for more information about how to install the program. Figure 1 describes the tape or cartridge. Figure 2 describes the file content of the program tape or cartridge.

Figure 1. Basic Material: Program Tape

Feature Number	Medium	Physical Volume	Tape Content	External Tape Label
5831*	6250 tape	1	DB2 DProp Q Capture for VM V7.4	DProp Q Capture VM
5832	3480 cart.	1	DB2 DProp Q Capture for VM V7.4	DProp Q Capture VM
5834	1/4 inch cart.	1	DB2 DProp Q Capture for VM V7.4	DProp Q Capture VM
6017	4mm cart.	1	DB2 DProp Q Capture for VM V7.4	DProp Q Capture VM

* Not available in Japan

Figure 2 (Page 1 of 2). Program Tape: File Content

Tape File	Content
1	Tape Header
2	Tape Header
3	Product Header

Figure 2 (Page 2 of 2). Program Tape: File Content

Tape File	Content
4	Product Memo
5	Service Apply Lists
6	PTFPARTs
7	DB2 DProp Q Capture for VM V7.4 Service
8	DB2 DProp Q Capture for VM V7.4 Service
9	DB2 DProp Q Capture for VM V7.4 Base Code
10	DB2 DProp Q Capture for VM V7.4 Executable Code

2.2 Optional Machine-Readable Material

There are no optional machine-readable materials for DB2 DProp Q Capture for VM V7.4.

2.3 Program Publications

The following sections identify the basic and optional publications for DB2 DProp Q Capture for VM V7.4.

2.3.1 Basic Program Publications

The publications for DB2 DProp Q Capture for VM V7.4 are included with the pre-requisite product, DB2 UDB Universal Database. No publications are included when you order the basic materials for DB2 DProp Q Capture for VM V7.4. For your convenience, the relevant publications are listed below. For additional copies, contact your IBM representative.

Figure 3. Basic Material: Unlicensed Publications

Publication Title	Form Number
<i>DB2 Replication and Event Publishing Guide and Event Publishing Guide and Reference</i>	SC18-7568
<i>DB2 Replication Guide and Reference Supplement for Q Capture VSE/VM</i>	

2.4 Microfiche Support

There is no microfiche for DB2 DProp Q Capture for VM V7.4.

2.5 Publications Useful During Installation

The publications listed in Figure 4 on page 5 may be useful during the installation of DB2 DProp Q Capture for VM V7.4. To order copies, contact your IBM representative.

Figure 4. Publications Useful During Installation / Service on VM/ESA Version 4.3

Publication Title	Form Number
<i>z/VM V4R3.0 VMSES/E Introduction and Reference</i>	GC24-5994
<i>z/VM V4R3.0 CMS Planning and Administration</i>	SC24-6042
<i>z/VM V4R3.0 CP Planning and Administration</i>	SC24-6043
<i>z/VM V4R3.0 Service Guide</i>	GC24-5993
<i>z/VM V4R3.0 CMS Command and Utility Reference</i>	SC24-6010
<i>z/VM V4R3.0 CP Command and Utility Reference</i>	SC24-6008
<i>z/VM V4R3.0 System Messages and Codes-CP</i>	GC24-6030
<i>z/VM V4R3.0 System Messages and Codes-CMS</i>	GC24-6031

3.0 Program Support

This section describes the IBM support available for DB2 DProp Q Capture for VM V7.4.

3.1 Preventive Service Planning

Before installing DB2 DProp Q Capture for VM V7.4, check with your IBM Support Center or use IBMLink (Service Link) to see whether there is additional Preventive Service Planning (PSP) information. To obtain this information, specify the following UPGRADE and SUBSET values:

Figure 5. PSP Upgrade and Subset ID

Retain			
COMPID	Release	Upgrade	Subset
5697F4201	741	DB2VSEVM740	DPRVM

3.2 Statement of Support Procedures

Report any difficulties you have using this program to your IBM Support Center. If an APAR is required, the Support Center will provide the address to which any needed documentation can be sent.

Figure 6 identifies the component ID (COMPID), Retain Release and Field Engineering Service Number (FESN) for DB2 DProp Q Capture for VM V7.4.

Figure 6. Component IDs

Retain			
COMPID	Release	Component Name	FESN
5697F4201	741	DB2 DProp Q Capture for VM V7.4	0404450

4.0 Program and Service Level Information

This section identifies the program and any relevant service levels of DB2 DProp Q Capture for VM V7.4. The program level refers to the APAR fixes incorporated into the program. The service level refers to the PTFs integrated. Information about the cumulative service tape is also provided.

4.1 Program Level Information

All closed APARs from previous versions/releases have been incorporated at the time of the product GA.

4.2 Service Level Information

Check the DB2VSEVM740 PSP bucket for any additional PTFs that should be installed or any additional install information.

4.3 Cumulative Service Tape

Cumulative service for DB2 DProp Q Capture for VM V7.4 is available through a monthly corrective service tape, Expanded Service Option, ESO.

5.0 Installation Requirements and Considerations

The following sections identify the system requirements for installing and activating DB2 DProp Q Capture for VM V7.4.

5.1 Hardware Requirements

There are no special hardware requirements for DB2 DProp Q Capture for VM V7.4.

5.2 Program Considerations

The following sections list the programming considerations for installing DB2 DProp Q Capture for VM V7.4 and activating its functions.

5.2.1 Operating System Requirements

DB2 DProp Q Capture for VM V7.4 supports the following VM operating systems:

- z/VM Version 4 Release 3, and later.

5.2.2 Other Program Product Requirements

The following Licensed Products are pre-requisites for DB2 DProp Q Capture for VM V7.4:

- DB2 Server for VSE & VM Version 7 Release 4.0 (5697-F42)
- DB2 UDB Universal Database Version 8 Release 2
- MQ Series Client for VM/ESA

DB2 DProp Q Capture for VM V7.4 requires C run-time library support provided by the appropriate level of the Language Environment for VM (5688-198).

5.2.3 Program Installation/Service Considerations

This section describes items that should be considered before you install or service DB2 DProp Q Capture for VM V7.4.

- VMSES/E is required to install and service this product.
- If multiple users install and maintain licensed products on your system, there may be a problem getting the necessary access to MAINT's 51D disk. If you find that there is contention for write access to the 51D disk, you can eliminate it by converting the Software Inventory from minidisk to Shared File System (SFS). See the *VMSES/E Introduction and Reference* manual, section 'Changing the Software Inventory to an SFS Directory', for information on how to make this change.

- Customers will install and service DB2 DProp Q Capture for VM V7.4 using a new user ID--5697F74B. This is the IBM suggested user ID name. You are free to change this to any user ID name you wish; however, a Product Parameter File (PPF) override must be created.

Note: It may be easier to make the above change during the installation procedure 6.2, “Plan Your Installation For DB2 DProp Q Capture for VM V7.4” step 6 on page 13, than after you have installed this product.

- The DB2 DProp Q Capture for VM V7.4 program runs in its own virtual machine, capturing changes for one and only one DB2 Server for VM database. If there are multiple databases for which you want to capture changes, you must define additional virtual machines for running the DB2 DProp Q Capture for VM V7.4 program. The charts in 5.3, “DASD Storage and user ID Requirements” define an initial virtual machine, CAPTMACH, to run the DB2 DProp Q Capture for VM V7.4 program. See 6.6, “Post-Installation Considerations (optional)” on page 26 for information on defining additional virtual machines.

5.3 DASD Storage and user ID Requirements

Figure 7 lists the user IDs and minidisks that are used to install and service DB2 DProp Q Capture for VM V7.4.

Important Installation Notes:

- User ID(s) and minidisks will be defined in 6.2, “Plan Your Installation For DB2 DProp Q Capture for VM V7.4” on page 12 and are listed here so that you can get an idea of the resources that you will need prior to allocating them.
- 5697F74B is a default user ID and can be changed. If you choose to change the name of the installation user ID you need to create a Product Parameter File (PPF) Override to reflect this change. This can be done in 6.2, “Plan Your Installation For DB2 DProp Q Capture for VM V7.4” step 6 on page 13.
- If you choose to install DB2 DProp Q Capture for VM V7.4 on a common user ID, the default minidisk addresses for DB2 DProp Q Capture for VM V7.4 may already be defined. If any of the default minidisks required by DB2 DProp Q Capture for VM V7.4 are already in use you will have to create an override to change the default minidisks for DB2 DProp Q Capture for VM V7.4 so they are unique.

Figure 7 (Page 1 of 2). DASD Storage Requirements for Target Minidisks

Minidisk owner (user ID)	Default Address	Storage in Cylinders		FB-512 Blocks	SFS 4K Blocks	Usage
		DASD	CYLS			Default SFS Directory Name
5697F74B	2B2	9345 3390 3380	12 12 12	2400	300	Contains all the base code shipped with DB2 DProp Q Capture for VM V7.4 VMSYS:5697F74B.DPROPR.OBJECT
5697F74B	2C2	9345 3390 3380	1 1 1	1200	150	Contains customization files. This disk may also be used for local modifications. VMSYS:5697F74B.DPROPR.SAMPLE
5697F74B	2D2	9345 3390 3380	15 15 15	4800	600	Contains serviced files VMSYS:5697F74B.DPROPR.DELTA
5697F74B	2A6	9345 3390 3380	1 1 1	1200	150	Contains AUX files and software inventory tables that represent the test service level of DB2 DProp Q Capture for VM V7.4 VMSYS:5697F74B.DPROPR.APPLYALT
5697F74B	2A2	9345 3390 3380	1 1 1	1200	150	Contains AUX files and software inventory tables that represent the service level of DB2 DProp Q Capture for VM V7.4 that is currently in production. VMSYS:5697F74B.DPROPR.APPLYPROD
5697F74B	200	9345 3390 3380	12 12 12	2400	300	Test build disk. This code will be copied to a production disk, so the production disk will also require this amount of free space. VMSYS:5697F74B.DPROPR.TBUILD
5697F74B	191	9345 3390 3380	4 4 4	4800	600	5697F74B user ID's 191 minidisk VMSYS:5697F74B.
CAPTMACH	300	9345 3390 3380	12 12 12	2400	300	Production code build disk. VMSYS:CAPTMACH.DPROPR.PBUILD
CAPTMACH	191	9345 3390 3380	1 1 1	1200	150	CAPTMACH user ID's 191 minidisk VMSYS:CAPTMACH.

Note: Cylinder values defined in this table are based on a 4K block size. FB-512 block and SFS values are derived from the 3380 cylinder values in this table. The FBA blocks are listed as 512 bytes but should be CMS formatted at 1K size. 2700 4K blocks are needed for SFS install.

6.0 Installation Instructions

This chapter describes the installation methods and the step-by-step procedures to install and activate DB2 DProp Q Capture for VM V7.4.

The step-by-step procedures are in two column format. The steps to be performed are in bold large numbers. Commands for these steps are on the left hand side of the page in bold print. Additional information for a command may exist to the right of the command. For more information about the two column format see 'Understanding Dialogs with the System' in the *VM/ESA Installation Guide*.

Each step of the installation instructions must be followed. Do not skip any step unless directed to do so.

Throughout these instructions, the use of IBM-supplied default minidisk addresses and user IDs is assumed. If you use different user IDs, minidisk addresses, or SFS directories to install DB2 DProp Q Capture for VM V7.4, adapt these instructions as needed for your environment.

Note!

The sample console output presented throughout these instructions was produced on a z/VM V4R3.0 system. If you are installing DB2 DProp Q Capture for VM V7.4 on a different VM/ESA system, the results obtained for some commands may differ from those depicted here.

6.1 VMSES/E Installation Process Overview

The following is a brief description of the main steps in installing DB2 DProp Q Capture for VM V7.4 using VMSES/E.

- Plan Your Installation

Use the VMFINS command to load several VMSES/E files from the product tape and to obtain DB2 DProp Q Capture for VM V7.4 resource requirements.

- Allocate Resources

The information obtained from the previous step is used to allocate the appropriate minidisks (or SFS directories) and user IDs needed to install and use DB2 DProp Q Capture for VM V7.4.

- Install the DB2 DProp Q Capture for VM V7.4 Product

Use the VMFINS command to load the DB2 DProp Q Capture for VM V7.4 product files from tape to the test BUILD and BASE minidisks/directories. VMFINS is then used to update the VM SYSBLDS file used by VMSES/E for software inventory management.

- Perform Post-installation Tasks

Information about file tailoring and initial activation of the program is presented in 6.6, "Post-Installation Considerations (optional)" on page 26.

- Place DB2 DProp Q Capture for VM V7.4 Files into Production

Once the product files have been tailored and the operation of DB2 DProp Q Capture for VM V7.4 is satisfactory, the product files are copied from the test BUILD disk(s) to production BUILD disk(s).

For a complete description of all VMSES/E installation options refer to *VMSES/E Introduction and Reference*.

6.2 Plan Your Installation For DB2 DProp Q Capture for VM V7.4

The VMFINS command will be used to plan the installation. This section has 2 main steps that will:

- load the first tape file, containing installation files
- generate a 'PLANINFO' file listing
 - all user ID/mdisks requirements
 - required products

To obtain planning information for your environment:

- 1** Log on as DB2 DProp Q Capture for VM V7.4 installation planner.
This user ID can be any ID that has read access to MAINT's 5E5 minidisk and write access to the MAINT 51D minidisk.
- 2** Mount the DB2 DProp Q Capture for VM V7.4 installation tape and attach it to the user ID at virtual address 181. The VMFINS EXEC requires the tape drive to be at virtual address 181.
- 3** Establish read access to the VMSES/E code.

**link MAINT 5e5 5e5 rr
access 5e5 b**

The 5E5 disk contains the VMSES/E code.

- 4** Establish write access to the Software Inventory disk.

**link MAINT 51d 51d mr
access 51d d**

The MAINT 51D disk is where the VMSES/E system-level Software Inventory and other dependent files reside.

Note: If another user already has the MAINT 51D minidisk linked in write mode (R/W), you will only obtain read access (R/O) to this minidisk. If this occurs, you will need to have that user re-link the 51D in read-only mode (RR), and then re-issue the above LINK and ACCESS commands. Do not continue with these procedures until a R/W link is established to the 51D minidisk.

- 5 Load the DB2 DProp Q Capture for VM V7.4 product control files to the 51D minidisk.

vmfins install info (nomemo)

The NOMEMO option will load the memos from the tape but will not issue a prompt to send them to the system printer. Specify the MEMO option if you want to be prompted for printing the memo.

This command will perform the following:

- load Memo-to-Users
- load various product control files, including the Product Parameter File (PPF) and the PRODPART files
- create VMFINS PRODLIST on your A-disk. The VMFINS PRODLIST contains a list of products on the installation tape.

```
VMFINS2760I VMFINS processing started
VMFINS1909I VMFINS PRODLIST created on your A-disk
VMFINS2760I VMFINS processing completed successfully
Ready;
```

- 6 Obtain resource planning information for DB2 DProp Q Capture for VM V7.4.

Notes:

- a. The product will **not** be loaded by the VMFINS command at this time.

vmfins install ppf 5697F74B {DPROPR | DPROPRSFS} (plan nomemo)

Use **DPROPR** for installing on minidisks or **DPROPRSFS** for installing in Shared File System directories.

The PLAN option indicates that VMFINS will perform requisite checking, plan system resources, and provide an opportunity to override the defaults in the product parameter file.

You can override any of the following:

- the name of the product parameter file
- the default user IDs
- minidisk/directory definitions

Notes:

- a. If you change the PPF name, a default user ID, or other parameters via a PPF override, you will need to use your changed values instead of those indicated (when appropriate), throughout the rest of the installation instructions, as well as the instructions for servicing DB2 DProp Q Capture for VM V7.4. For example, you will need to specify your PPF override file name instead of 5697F74B for certain VMSES/E commands.
- b. If you are not familiar with creating PPF overrides using VMFINS, you should review the 'Using the Make Override Panel' section in Chapter 3 of the *VMSES/E Introduction and Reference* before you continue.
- c. For more information about changing the VMSYS file pool name refer to Chapter 3 in the *VMSES/E Introduction and Reference*.

```
VMFINS2767I Reading VMFINS DEFAULTS B for additional options
VMFINS2760I VMFINS processing started
VMFINS2601R Do you want to create an override for :PPF 5697F74B DPROPR
             :PRODID. 5697F74B%DPROPR?
             Enter 0 (No), 1 (Yes) or 2 (Exit)
0
VMFINS2603I Processing product :PPF 5697F74B DPROPR :PRODID
             5697F74B%DPROPR
VMFREQ1909I 5697F74B PLANINFO created on your A-disk
VMFREQ2805I Product :PPF 5697F74B DPROPR :PRODID
5697F74B%DPROPR
             has passed requisite checking
VMFINT2603I Planning for the installation of product :PPF 5697F74B
DPROPR
             :PRODID 5697F74B%DPROPR
VMFRMT2760I VMFRMT processing started
VMFRMT2760I VMFRMT processing completed successfully
VMFINS2760I VMFINS processing completed successfully
```

Note!

Complete this step only if you received message VMFREQ2806W.

If you receive the following VMFREQ2806W message, you must do some additional processing.

```
VMFREQ2806W The following requisites for product 5697F74B component
              DPR0PR are not satisfied
```

Type	Product	Component	PTF
-----	-----	-----	-----
Requisite	5697F74A		

This message indicates that 5697F42, product DB2 Server for VSE & VM is a pre-requisite product for DB2 DProp Q Capture for VM V7.4. It must be installed before you continue the install for DB2 DProp Q Capture for VM V7.4.

- 7** Review the install message log (\$VMFINS \$MSGLOG). If necessary, correct any problems before going on. For information about handling specific error messages, see *VM/ESA: System Messages and Codes*, or use on-line HELP.

vmfview install

6.3 Allocate Resources for Installing DB2 DProp Q Capture for VM V7.4

Use the planning information in the 5697F74B PLANINFO file, created in the **PLAN** step (6.2, "Plan Your Installation For DB2 DProp Q Capture for VM V7.4" on page 12), to:

- Create the 5697F74B and CAPTMACH user directories for minidisk install

OR

- Create the 5697F74B and CAPTMACH user directories for SFS install

6.3.1 Installing DB2 DProp Q Capture for VM V7.4 on Minidisk

- 1** Obtain the user directory from the 5697F74B PLANINFO file.

Notes:

- a. The user directory entry is located in the resource section of the PLANINFO file, at the bottom; these entries will contain all of the links and privilege classes necessary for the 5697F74B and CAPTMACH user IDs. Use the directory entry found in PLANINFO as a model of input to your system directory.
- b. When adding the directory entry for the CAPTMACH, keep in mind the following about the sample directory statements in the PLANINFO file.

IUCV *IDENT CAPTURE LOCAL

The CAPTMACH must be authorized in its directory to connect to the system service ***IDENT**. Authorization is granted by the IUCV entry in the CAPTMACH directory.

CAPTURE Refers to a unique name for each database DB2 DProp Q Capture for VM V7.4 is being used with. Specification of this name is in the file *CAPTURE ASNPARM.S*.

LOCAL Identifies the resource as a LOCAL resource.

- c. The Q Capture machine must run in XC mode because dataspace are being used. The following statements need to be added to the CP directory for the Q Capture machine:

MACHINE XC

XCONFIG ACCESSLIST ALSIZE xxxx

XCONFIG ADDRSPACE MAXNUMBER nnnn TOTSIZe nnnnG

The xxxx is the number of dataspace that can be accessed at once. The machine is authorized to create and delete up to nnnn dataspace where the total size of all dataspace cannot exceed nnnnG(gigabytes).

- d. The MQ Client for VM and TCP/IP Client disks need to be linked in. For example,

LINK MAINT 193 193 RR

LINK TCPMAINT 592 592 RR

- 2** Add the MDISK statements to the directory entries for 5697F74B and CAPTMACH. Use Figure 7 on page 9 to obtain the minidisk requirements.
- 3** Add the 5697F74B and CAPTMACH directories to the system directory. Change the passwords for 5697F74B and CAPTMACH from xxxxx to a valid password, in accordance with your security guidelines.

- 4 Place the new directories on-line using VM/Directory Maintenance (DIRMAINT) or an equivalent CP directory maintenance method.

Note

All minidisks for the 5697F74B and CAPTMACH user IDs must be formatted before installing DB2 DProp Q Capture for VM V7.4.

6.3.2 Installing DB2 DProp Q Capture for VM V7.4 in SFS Directories

- 1 Obtain the user directory from the 5697F74B PLANINFO file.

Notes:

- a. The user directory entry is located in the resource section of the PLANINFO file, at the bottom; these entries will contain all of the links and privilege classes necessary for the 5697F74B and CAPTMACH user IDs. Use the directory entries found in PLANINFO as a model of input to your system directory.
- b. When adding the directory entry for the CAPTMACH, keep in mind the following about the sample directory statements in the PLANINFO file.

IUCV *IDENT CAPTURE LOCAL

The CAPTMACH must be authorized in its directory to connect to the system service ***IDENT**. Authorization is granted by the IUCV entry in the CAPTMACH directory.

CAPTURE Refers to a unique name for each database DB2 DProp Q Capture for VM V7.4 is being used with. Specification of this name is in the file *CAPTURE ASNPARMS*.

LOCAL Identifies the resource as a LOCAL resource.

- c. The Q Capture machine must run in XC mode because dataspace are being used. The following statements need to be added to the CP directory for the Q Capture machine:

MACHINE XC

XCONFIG ACCESSLIST ALSIZE xxxx

XCONFIG ADDRSPACE MAXNUMBER nnnn TOTSIZEnnnnG

The xxxx is the number of dataspace that can be accessed at once. The machine is authorized to create and delete up to nnnn dataspace where the total size of all dataspace cannot exceed nnnnG(gigabytes).

- d. The MQ Client for VM and TCP/IP Client disks need to be linked in. For example,

LINK MAINT 193 193 RR

LINK TCPMAINT 592 592 RR

- 2** Add the 5697F74B and CAPTMACH directories to the system directory. Change the passwords for 5697F74B and CAPTMACH from xxxxx to a valid password, in accordance with your security guidelines.
- 3** Place the new directories on-line using VM/Directory Maintenance (DIRMAINT) or an equivalent CP directory maintenance method.
- 4** An SFS install will also require the following steps:
 - a** Determine the number of 4K blocks that are required for SFS directories by adding up the 4K blocks required for each SFS directory you plan to use.

If you intend to use all of the default DB2 DProp Q Capture for VM V7.4 SFS directories, the 4K block requirements for each are summarized in Figure 7 on page 9.

This information will be used when enrolling the 5697F74B to the VMSYS filepool.
 - b** Enroll user 5697F74B in the VMSYS filepool using the ENROLL USER command:

```
ENROLL USER 5697F74B VMSYS: (BLOCKS blocks
```

where *blocks* is the number of 4K blocks that you calculated in the previous step.

Note: This must be done from a user ID that is an administrator for VMSYS: filepool.
 - c** Determine if there are enough blocks available in the filepool to install DB2 DProp Q Capture for VM V7.4. This information can be obtained from the QUERY FILEPOOL STORGRP command. If the number of blocks free is smaller than the total 4K blocks needed to install DB2 DProp Q Capture for VM V7.4 in the appropriate storage group you will need to add space to the filepool. (The default storage group used on the above ENROLL USER is group 2). See the *VM/ESA SFS and CRR Planning, Administration, and Operation* manual for information on adding space to a filepool.
 - d** Create the necessary subdirectories listed in the 5697F74B PLANINFO file using the CREATE DIRECTORY command.

set filepool vmsys:
create directory *dirid*

dirid is the name of the SFS directory you are creating. An example of the create command is:

```
create directory vmsys:5697F74B.Dpropr  
create directory vmsys:5697F74B.Dpropr.object  
:
```

If necessary, see the *VM/ESA CMS Command Reference* manual for more information about the CREATE DIRECTORY command.

A complete list of default Dpropr SFS directories is provided in Figure 7 on page 9.

- e** Give the **CAPTMACH** user ID READ authority to the general-use test build directory, using the GRANT AUTHORITY command.

grant auth vmsys:5697F74B.Dpropr.tbuid. to CAPTMACH (read newread

If necessary, see the *VM/ESA CMS Command Reference* manual for more information about the GRANT AUTHORITY command.

- f** If you intend to use an SFS directory as the work space for the 5697F74B user ID, include the following IPL control statement in the 5697F74B directory entry:

IPL CMS PARM FILEPOOL VMSYS

This will cause CMS to automatically access the 5697F74B's top directory as file mode A.

6.4 Install DB2 DProp Q Capture for VM V7.4

The *ppfname* used throughout these installation instructions is **5697F74B**, which assumes you are using the PPF supplied by IBM for DB2 DProp Q Capture for VM V7.4. If you have your own PPF override file for DB2 DProp Q Capture for VM V7.4, you should use your file's *ppfname* instead of **5697F74B**. The *ppfname* you use should be used **throughout** the rest of this procedure.

The *compname* used throughout these installation instructions is either **DPROPR** or **DPROPRSFS**, which assumes you are using the component name within the 5697F74B PPF file. If you specify your own *ppfname*, you should use the *compname* from that file instead of **DPROPR** or **DPROPRSFS**. The *compname* you use should be used **throughout** the rest of this procedure.

- 1** Logon to the installation user ID **5697F74B**.
- 2** Create a PROFILE EXEC that will contain the ACCESS commands for MAINT 5E5 and 51D minidisks.


```
xedit profile exec a
====> input /**/
====> input 'access 5e5 b'
====> input 'access 51d d'
====> file
```

If either 5E5 or 51D is in a shared file system (SFS) then substitute your SFS directory name in place of the 5E5 and 51D in the access command.

3 Run the profile to access MAINT's minidisks.

profile

4 If the Software Inventory disk (51D) was accessed R/O (read only) then establish write access to the Software Inventory disk.

Note: If the MAINT 51D minidisk was accessed R/O, you will need to have the user who has it linked R/W link it as R/O. You then can issue the following commands to obtain R/W access to it.

```
link MAINT 51d 51d mr
access 51d d
```

5 Have the DB2 DProp Q Capture for VM V7.4 installation tape mounted and attached to 5697F74B at virtual address 181. The VMFINS EXEC requires the tape drive to be at virtual address 181.

6 Install DB2 DProp Q Capture for VM V7.4.

Notes:

- a. If you have already created a PPF override file, you should specify your override file name, in place of the default PPF name (5697F74B), after the **PPF** keyword for the following VMFINS command.
- b. You may be prompted for additional information during VMFINS INSTALL processing depending on your installation environment. If you are unsure how to respond to a prompt, refer to the 'Installing Products with VMFINS' and 'Install Scenarios' chapters in the *VMSES/E Introduction and Reference* to decide how to proceed.
- c. VMFINS will access all disks needed during the installation, please ensure that your installation id has your SQLMACHs 195 disk linked before running the next step.

```
vmfins install ppf 5697F74B {DPROPR | DPROPRSFS} (nomemo nolink
```

Use **DPROPR** for installing on minidisks or **DPROPRSFS** for installing in Shared File System directories.

The NOLINK option indicates that you do not want VMFINS to link to the appropriate minidisks, only access them if not accessed.

```

VMFINS2767I Reading VMFINS DEFAULTS B for additional options
VMFINS2760I VMFINS processing started
VMFINS2601R Do you want to create an override for :PPF 5697F74B DPRPR
:PRODID. 5697F74B%DPROPR?
Enter 0 (No), 1 (Yes) or 2 (Exit)
0
VMFINS2603I Processing product :PPF 5697F74B DPRPR :PRODID
5697F74B%DPROPR
VMFREQ1909I 5697F74B PLANINFO created on your A-disk
VMFREQ2805I Product :PPF 5697F74B DPRPR :PRODID
5697F74B%DPROPR
has passed requisite checking
VMFINT2603I Installing product :PPF 5697F74B DPRPR :PRODID
5697F74B%DPROPR
VMFSET2760I VMFSETUP processing started
VMFUTL2205I Minidisk|Directory Assignments:
String Mode Stat Vdev Label/Directory
VMFUTL2205I LOCALSAM E R/W 2C2 SES2C2
VMFUTL2205I APPLY F R/W 2A6 SES2A6
VMFUTL2205I G R/W 2A2 SES2A2
VMFUTL2205I DELTA H R/W 2D2 SES2D2
VMFUTL2205I BUILD0 I R/W 200 SES200
VMFUTL2205I BASE J R/W 2B2 SES2B2
VMFUTL2205I SYSTEM K R/O 195 DB2195
VMFUTL2205I ----- A R/W 191 SES191
VMFUTL2205I ----- B R/O 5E5 MNT5E5
VMFUTL2205I ----- D R/W 51D SES51D
VMFUTL2205I ----- S R/O 190 MNT190
VMFUTL2205I ----- Y/S R/O 19E MNT19E
VMFSET2760I VMFSETUP processing completed successfully
VMFREC2760I VMFREC processing started
VMFREC1852I Volume 1 of 1 of INS TAPE 9800
VMFREC1851I (1 of 6) VMFRCAXL processing AXLIST
VMFRCX2159I Loading 0 part(s) to DELTA 2D2 (H)
VMFREC1851I (2 of 6) VMFRCPTF processing PARTLST
VMFRCP2159I Loading 0 part(s) to DELTA 2D2 (H)
VMFREC1851I (3 of 6) VMFRCOM processing DELTA
VMFRC2159I Loading 0 part(s) to DELTA 2D2 (H)
VMFREC1851I (4 of 6) VMFRCALL processing APPLY
VMFRC2159I Loading part(s) to APPLY 2A6 (F)
VMFRC2159I Loaded 1 part(s) to APPLY 2A6 (F)
VMFREC1851I (5 of 6) VMFRCALL processing BASE
VMFRC2159I Loading part(s) to BASE 2B2 (J)
VMFRC2159I Loaded 17 part(s) to BASE 2B2 (J)
VMFREC1851I (6 of 6) VMFRCALL processing BUILD
VMFRC2159I Loading part(s) to BUILD0 200 (I)
VMFRC2159I Loaded 12 part(s) to BUILD0 200 (I)
VMFREC2760I VMFREC processing completed successfully
VMFINT2603I Product installed
VMFINS2760I VMFINS processing completed successfully

```

- 7** Review the install message log (\$VMFINS \$MSGLOG). If necessary, correct any problems before going on. For information about handling specific error messages, see *VM/ESA: System Messages and Codes*, or use on-line HELP.

vmfview install

6.4.1 Update Build Status Table for DB2 DProp Q Capture for VM V7.4

- 1 Update the VM SYSBLDS software inventory file for DB2 DProp Q Capture for VM V7.4.

vmfins build ppf 5697F74B {DPROPR | DPROPRSFS} (serviced nolink

Use **DPROPR** for installing on minidisks or **DPROPRSFS** for installing in Shared File System directories.

The SERVICED option will build any parts that were not built on the installation tape (if any) and update the Software Inventory build status table showing that the product 5697F74B has been built.

- 2 Review the install message log (\$VMFINS \$MSGLOG). If necessary, correct any problems before going on. For information about handling specific error messages, see *VM/ESA: System Messages and Codes*, or use on-line HELP.

vmfview install

6.5 Place DB2 DProp Q Capture for VM V7.4 Into Production

6.5.1 Customize the CAPTMACH user ID

Customizing the CAPTMACH user ID involves setting up the CAPTMACH user ID as a user of a database. Your installation may have a standard set-up that you should follow instead of the following instructions.

- 1 Logon to the Capture machine, CAPTMACH.

If you are using minidisks you need to make sure that the 191 A-disk has been formatted.

- 2 Access the database production disk or directory.

access {vdev:epv|dirid}. q

vdev is the address the database machine production minidisk, or dirid is the name of the database machine production SFS directory.

- 3 Copy the sample PROFILE EXEC for a user machine.

copyfile sqluser profile q profile exec a

You may need to add local environmental commands. Obtain this information from your system programming department.

4 Make the DB2 Server for VM message repository available.

set language ameng (add ari user

6.5.2 Copy DB2 DProp Q Capture for VM V7.4 Files Into Production

1 Put the DB2 DProp Q Capture for VM V7.4 code on the production build disk.

a If installing using minidisks

link 5697F74B 200 200 rr

access 200 e

access 300 f

vmfcopy * * e = = f (prodid 5697F74B%DPROPR olddate replace

The VMFCOPY command will update the VMSES PARTCAT file on the 300 disk.

b If installing using Shared File System

access 5697F74B.DPROPR.tbuild e

access CAPTMACH.DPROPR.pbuild f

vmfcopy * * e = = f (prodid 5697F74B%DPROPR olddate replace

The VMFCOPY command will update the VMSES PARTCAT file on the production SFS directory.

6.5.3 Load the DB2 DProp Q Capture for VM V7.4 Package files to a database

To load the DB2 DProp Q Capture for VM V7.4 package, the ASNLOAD EXEC must be used. This exec uses the DBS Utility program RELOAD PACKAGE in multiple user mode to load the package files. The ASNLOAD EXEC assumes that the user ID is SQLDBA and that the password is SQLDBAPW. If the password has been changed, it should be reassigned to SQLDBAPW before running ASNLOAD. Alternatively, update the CONNECT statement in the ASNLOAD EXEC to specify the current password for SQLDBA.

You must first use the SQLINIT EXEC to specify the name of the database that you are loading the package to.

sqlinit dbname(*dbname*)

asnload *dbname*

dbname is the database you are loading the package files to.

6.5.4 Starting DB2 DProp Q Capture for VM V7.4

Note!

Prior to running DB2 DProp Q Capture for VM V7.4, DB2 UDB Universal Database Version 8 Release 2 must be installed and the Replication Center administration functions of defining at least one replication source and subscription must be performed. If this is not done, DB2 DProp Q Capture for VM V7.4 will not start successfully and you will be unable to perform installation verification.

The following MQ Server information needs to be inserted in the LASTING GLOBALV:

GLOBALV SELECT CENV SETLP MQSERVER <channel name>/TCP/<server-address(port)>

For example, GLOBALV SELECT CENV SETLP MQSERVER VM2MQ/TCP/9.26.78.125(1414).

For instructions on DB2 DProp Q Capture for VM V7.4 invocation, parameters, and operation, see the DB2 DProp Q Capture for VM V7.4 information in the *DB2 Replication and Event Publishing Guide and Event Publishing Guide and Reference*, SC18-7568, and its supplement for Q Capture VSE/VM.

Additionally, you may need to customize the **CAPTURE ASNPARMs** parameter file to specify the language file that DB2 DProp Q Capture for VM V7.4 will use for displaying messages. The default language is American English (ASNQS001). To issue messages in a different language, change the LANGUAGE parameter in the CAPTURE ASNPARMs file and file it on the Capture virtual machine's A-disk. Supported languages include:

Membername	Description
ASNQS001	American English
ASNQS002	Upper case English
ASNQS003	French
ASNQS004	German
ASNQD001	Japanese

6.5.5 Installation Verification Procedure for DB2 DProp Q Capture for VM V7.4

Once the DB2 DProp Q Capture for VM V7.4 is started, you should see an informational message *ASN0572I The program initialized successfully* on the CAPTMACH console. It means the DB2 DProp Q Capture for VM V7.4 has been able to connect to the DB2 database and is running successfully. Once DB2 DProp Q Capture for VM V7.4 is started, it will continue to run until the STOP operator command is issued. At this time, you may also look at the DB2 DProp Q Capture for VM V7.4 trace table, ASN.IBMQREP_CAPTRACE, to verify that the same message is logged into the table.

6.6 Post-Installation Considerations (optional)

DB2 DProp Q Capture for VM V7.4 runs in a virtual machine capturing changes for one and only one DB2 Server for VM database. Additional virtual machines must be defined if there is more than one DB2 Server for VM database in which you want to capture changes. They can be modeled after the CAPTMACH user ID, with the following changes:

- Change the link to the SQLMACH 195 Production disk to the 195 disk of the appropriate database.
- Update the *IDENT statement in the CP directory of the new virtual machine. You need to specify a unique resource ID for each virtual machine running DB2 DProp Q Capture for VM V7.4.
- Customize the CAPTURE ASNPARMS parameter file for the virtual machine. You will need to update the ENQ_NAME parameter with the name specified in the *IDENT above.
- Follow step 6.5.3, “Load the DB2 DProp Q Capture for VM V7.4 Package files to a database” specifying the appropriate database name.

Note that the additional virtual machines can all link to the CAPTMACH 300 production disk to gain access to the DB2 DProp Q Capture for VM V7.4 code.

<p>DB2 DProp Q Capture for VM V7.4 is now installed and built on your system.</p>
--

7.0 Migration Instructions

The previous versions of Data Propagator Capture for VM cannot be migrated to Data Propagator Q Capture. Follow the Installation Instructions, see 6.0, "Installation Instructions" on page 11, to complete the installation.

8.0 Service Instructions

This section of the Program Directory contains the procedure to install CORrective service to DB2 DProp Q Capture for VM V7.4. VMSES/E is used to install service for DB2 DProp Q Capture for VM V7.4.

To become more familiar with service using VMSES/E, you should read the introductory chapters in the *VMSES/E Introduction and Reference*. This manual also contains the command syntax for the VMSES/E commands listed in the procedure.

Note: Each step of the servicing instructions must be followed. Do not skip any step unless directed to do so. All instructions showing accessing of disks assume the use of default minidisk addresses. If different minidisk addresses are used, or if using a shared file system, change the instructions appropriately.

8.1 VMSES/E Service Process Overview

The following is a brief description of the main steps in servicing DB2 DProp Q Capture for VM V7.4 using VMSES/E.

- Setup Environment
Access the software inventory disk. Use VMFSETUP command to establish the correct minidisk access order.
- Merge Service
Use the VMFMRDSK command to clear the alternate apply disk before receiving new service. This allows you to easily remove the new service if a serious problem is found.
- Receive Service
The VMFREC command receives service from the delivery media and places it on the Delta disk.
- Apply Service
The VMFAPPLY command updates the version vector table (VVT), which identifies the service level of all the serviced parts. In addition, AUX files are generated from the VVT for parts that require them.
- Reapply Local Service (if applicable)
All local service (mods) must be entered into the software inventory to allow VMSES/E to track the changes and build them into the system. Refer to Chapter 7 in the *VM/ESA Service Guide* for this procedure.
- Build New Levels
The build task generates the serviced level of an object and places the new object on a test BUILD disk.
- Place the New Service into Production

Once the service is satisfactorily tested, it should be put into production by copying the new service to the production disk.

- Load the DB2 DProp Q Capture for VM V7.4 Package file

8.2 Servicing DB2 DProp Q Capture for VM V7.4

8.2.1 Prepare to Receive Service

The *ppfname* used throughout these servicing instructions is **5697F74B**, which assumes you are using the PPF supplied by IBM for DB2 DProp Q Capture for VM V7.4. If you have your own PPF override file for DB2 DProp Q Capture for VM V7.4, you should use your file's *ppfname* instead of **5697F74B**. The *ppfname* you use should be used **throughout** the rest of this procedure, unless otherwise stated.

The *compname* used throughout these servicing instructions is either **DPROPR** or **DPROPRSFS**, which assumes you are using the component name within the 5697F74B PPF file. If you specify your own *ppfname*, you should use the *compname* from that file instead of **DPROPR** or **DPROPRSFS**. The *compname* you use should be used **throughout** the rest of this procedure.

1 Logon to DB2 DProp Q Capture for VM V7.4 service user ID **5697F74B**

2 If the Software Inventory disk (51D) was accessed R/O (read only) then establish write access to the Software Inventory disk.

Note: If the MAINT 51D minidisk was accessed R/O, you will need to have the user that has it accessed R/W link it R/O. You then can issue the following commands to obtain R/W access to it.

**link MAINT 51d 51d mr
access 51d d**

The 51D minidisk is where the VMSES/E Software Inventory files and other product dependent files reside.

3 Have the DB2 DProp Q Capture for VM V7.4 CORrective service tape mounted and attached to **5697F74B**.

4 Establish the correct minidisk access order.

vmfsetup 5697F74B {DPROPR | DPROPRSFS}

5697F74B is the PPF that was shipped with the product. If you have your own PPF override you should substitute your PPF name for 5697F74B.

Use **DPROPR** for installing on minidisks or **DPROPRSFS** for installing in Shared File System directories.

- 5 Receive the documentation. VMFREC, with the INFO option, loads the documentation and displays a list of all the products on the tape.

Electronic Service

If you are receiving service from Service Link (electronic service) see Appendix A, 'Receiving Service for VMSES Envelopes', section Receive Service Documentation, in the *VM/ESA Service Guide*, then return back to this program directory and continue with step 7 below.

vmfrec info

This command will load the service memo to the 191 disk.

- 6 Check the receive message log (\$VMFREC \$MSGLOG) for warning and error messages.

vmfview receive

Also make note of which products and components have service on the tape. To do this, use the PF5 key to show all status messages which identify the products on the tape.

- 7 Merge previously applied service to ensure that you have a clean alternate apply disk for new service.

vmfmrdsk 5697F74B {DPROPR | DPROPRSFS} apply

Use **DPROPR** for installing on minidisks or **DPROPRSFS** for installing in Shared File System directories.

This command clears the alternate APPLY disk.

- 8 Review the merge message log (\$VMFMRD \$MSGLOG). If necessary, correct any problems before going on. For information about handling specific error messages, see *VM/ESA: System Messages and Codes*, or use on-line HELP.

vmfview mrd

8.2.2 Receive the Service

Electronic Service

If you are receiving service from Service Link (electronic service) see Appendix A, 'Receiving Service for VMSES Envelopes', section Receive the Service, in the *VM/ESA Service Guide*. Then return back to this program directory and continue with section 8.2.3, "Apply the Service."

1 Receive the service.

vmfrec ppf 5697F74B {DPROPR | DPROPRSFS}

Use **DPROPR** for installing on minidisks or **DPROPRSFS** for installing in Shared File System directories.

This command receives service from your service tape. All new service is loaded to the DELTA disk.

2 Review the receive message log (\$VMFREC \$MSGLOG). If necessary, correct any problems before going on. For information about handling specific error messages, see *VM/ESA: System Messages and Codes*, or use on-line HELP.

vmfview receive

8.2.3 Apply the Service

1 Apply the new service.

vmfapply ppf 5697F74B {DPROPR | DPROPRSFS}

Use **DPROPR** for installing on minidisks or **DPROPRSFS** for installing in Shared File System directories.

This command applies the service that you just received. The version vector table (VVT) is updated with all serviced parts and all necessary AUX files are generated on the alternate apply disk.

You must review the VMFAPPLY message log if you receive a return code (RC) of 4, as this may indicate that you have local modifications that need to be reworked.

- 2 Review the apply message log (\$VMFAPP \$MSGLOG). If necessary, correct any problems before going on. For information about handling specific error messages, see *VM/ESA: System Messages and Codes*, or use on-line HELP.

vmfview apply

Note

If you get the message VMFAPP2120W then re-apply any local modifications before building the new DB2 DProp Q Capture for VM V7.4. Refer to chapter 7 in the *VM/ESA Service Guide*. Follow the steps that are applicable to your local modification.

The following substitutions need to be made:

- **esalcl** should be **5697F74B**
- **esa** should be **5697F74B**
- *compname* should be **DPROPR** or **DPROPRSFS** (minidisk or SFS)
- *appid* should be **5697F74B**
- *fm-local* should be the fm of 2C2
- *fm-applyalt* should be the fm of 2A6
- **outmode localmod** should be **outmode localsam**

If you have changed any of the installation parameters through a PPF override, you need to substitute your changed values where applicable.

Keep in mind that when you get to the "Return to the Appropriate Section to Build Remaining Objects" or "Rebuild Remaining Objects" step in the *VM/ESA Service Guide*, you should return back to this program directory at 8.2.4, "Update the Build Status Table."

8.2.4 Update the Build Status Table

- 1 Update the Build Status Table with serviced parts.

vmfbld ppf 5697F74B {DPROPR | DPROPRSFS} (status

Use **DPROPR** for installing on minidisks or **DPROPRSFS** for installing in Shared File System directories.

This command updates the Build Status Table.

Note

If the \$PPF files have been serviced you will get the following prompt:

VMFBLD2185R The following source product parameter files have been serviced:

VMFBLD2185R 5697F74B \$PPF

VMFBLD2185R When source product parameter files are serviced, all product parameter files built from them must be recompiled using VMFPPF before VMFBLD can be run.

VMFBLD2185R Enter zero (0) to have the serviced source product parameter files built to your A-disk and exit VMFBLD so you can recompile your product parameter files with VMFPPF.

VMFBLD2185R Enter one (1) to continue only if you have already recompiled your product parameter files with VMFPPF.

0

Enter a 0 and complete the following steps before you continue.

VMFBLD2188I Building 5697F74B \$PPF
on 191 (A) from level \$PFnnnnn

vmfppf 5697F74B *

Note: If you have created your own PPF override then use your PPF name instead of 5697F74B.

**copyfile 5697F74B \$PPF a = = d (olddate replace
erase 5697F74B \$PPF a**

Note: Do not use your own PPF name in place of 5697F74B for the COPYFILE and ERASE commands.

vmfbld ppf 5697F74B {DPROPR | DPROPRSFS} (status

1

Re-issue VMFBLD to complete updating the build status table.

Use **DPROPR** for installing on minidisks or **DPROPRSFS** for installing in Shared File System directories. When you receive the prompt that was previously displayed, enter a 1 to continue.

- 2 Use VMFVIEW to review the build status messages, and see what objects need to be built.

vmfview build

8.2.5 Build Serviced Objects

- 1 Rebuild DB2 DProp Q Capture for VM V7.4 serviced parts.

vmfbld ppf 5697F74B {DPROPR | DPROPRSFS} (serviced

Use **DPROPR** for installing on minidisks or **DPROPRSFS** for installing in Shared File System directories.

Notes:

1. If your software inventory disk (51D) is not owned by the MAINT user ID then make sure the VMSESE PROFILE reflects the correct owning user ID.
2. Rebuilding DB2 DProp Q Capture for VM V7.4 requires access to the SCEELKED TXTLIB.

- 2 Review the build message log (\$VMFBLD \$MSGLOG). If necessary, correct any problems before going on. For information about handling specific error messages, see *VM/ESA: System Messages and Codes*, or use on-line HELP.

vmfview build

8.3 Place the New DB2 DProp Q Capture for VM V7.4 Service Into Production

8.3.1 Copy the New DB2 DProp Q Capture for VM V7.4 Serviced Files Into Production

- 1 Logon to CAPTMACH to put DB2 DProp Q Capture for VM V7.4 code on the production code build disk.

a If installing using minidisks

link 5697F74B 200 200 rr
access 200 e
access 300 f

The VMFCOPY command will update the VMSES PARTCAT file on the 300 disk.

vmfcopy * * e = = f (prodid 5697F74B%DPROPR olddate replace

b If installing using Shared File System

access 5697F74B.DPROPR.tbuid e
access CAPTMACH.DPROPR.pbuid f
vmfcopy * * e = = f (prodid 5697F74B%DPROPR olddate replace

The VMFCOPY command will update the VMSES PARTCAT file on the production SFS directory.

8.3.2 Load the DB2 DProp Q Capture for VM V7.4 Package files to a database

The DB2 DProp Q Capture for VM V7.4 packages must be reloaded in all databases if there is a service update to the package. To load the DB2 DProp Q Capture for VM V7.4 packages, the ASNLOAD EXEC must be used. This exec uses the DBS Utility program RELOAD PACKAGE in multiple user mode to load the package files. The ASNLOAD EXEC assumes that the user ID is SQLDBA and that the password is SQLDBAPW. If the password has been changed, it should be reassigned to SQLDBAPW before running ASNLOAD. Alternatively, update the CONNECT statement in the ASNLOAD EXEC to specify the current password for SQLDBA.

You must first use the SQLINIT EXEC to specify the name of the database that you are loading the package to.

sqlinit dbname(*dbname*)
asnload *dbname*

dbname is the database you are loading the package files to.


You have finished servicing DB2 DProp Q Capture for VM V7.4.

Reader's Comments

DataPropagator Q Capture for VM Version 7 Release 4.0

You may use this form to comment about this document, its organization, or subject matter. Please understand that your feedback is of importance to IBM, but IBM makes no promises to always provide a response to your feedback.

For each of the topics below please indicate your satisfaction level by circling your choice from the rating scale. If a statement does not apply, please circle N.

RATING SCALE						
very satisfied					very dissatisfied	not applicable
1	2	3	4	5	N	

	Satisfaction					
Ease of product installation	1	2	3	4	5	N
Time required to install the product	1	2	3	4	5	N
Contents of program directory	1	2	3	4	5	N
Readability and organization of program directory tasks	1	2	3	4	5	N
Necessity of all installation tasks	1	2	3	4	5	N
Accuracy of the definition of the installation tasks	1	2	3	4	5	N
Technical level of the installation tasks	1	2	3	4	5	N
Installation verification procedure	1	2	3	4	5	N
Ease of customizing the product	1	2	3	4	5	N
Ease of migrating the product from a previous release	1	2	3	4	5	N
Ease of putting the system into production after installation	1	2	3	4	5	N
Ease of installing service	1	2	3	4	5	N

- Did you order this product as an independent product or as part of a package?

- Independent
- Package

What type of package was ordered?

- CustomPac
 - FunctionPac
 - SystemPac
- System Delivery Offering (SDO)
- Other - Please specify type: _____

- Is this the first time your organization has installed this product?
 - Yes
 - No
- Were the people who did the installation experienced with the installation of VM products using VMSES/E?
 - Yes
 - How many years of experience do they have? _____
 - No
- How long did it take to install this product? _____
- If you have any comments to make about your ratings above, or any other aspect of the product installation, please list them below:

Please provide the following contact information:

Name and Job Title

Organization

Address

Telephone

Thank you for your participation.

Please send the completed form to the following address, or give to your IBM representative who will forward it to the DataPropagator Q Capture for VM Development group:

IBM Canada Ltd.
 DB2 Server for VSE & VM
 B4/240/8200/MKM
 8200 Warden Avenue
 Markham, Ontario, Canada. L6G 1C7



Program Number: 5697-F42 5831
5832
5834
6017

Printed in U.S.A.

GI10-5000-02

