Desk Station V+ (PA2710)

FUNCTION: To expand external interface capabilities by using Select
                Bay for Modular CD-ROM/FDD, (1) 5¬" Half-height Drive
Bay,
                (2) Full length PCI/ISA combination slots, (1) PCI Short
                slot, built-in SCSI-II, and (2) Type III PC Card slots.

COMPATIBILITY: Tecra 710CDT, Tecra 720CDT. (Not compatible with Tecra
                700CS/CT).

DIMENSIONS: OVERALL: 6.0"H x 16.2"W x 14.5"D

                EXPANSION SLOTS:
                     Slot One   (PCI/ISA): 25.4 x 340 x 122mm
                                            (1.0" x 13.39" x 4.8")
                     Slot Two   (PCI/ISA): 25.4 x 340 x 122mm
                                            (1.0" x 13.39" x 4.8")
                     Slot Three (PCI only): 25.4 x 234.63 x 122mm
                                            (1.0" x 9.24" x 4.8")

                PC CARD SLOTS: (2) Type III (10.5mm high)
                                   with CardBus support

                5¬" HALF HEIGHT EXPANSION BAY:
                     SCSI-II or IDE Interface
                     Maximum device size: 42 x 145 x 233mm
                                           (1.65"H x 5.71"W x 9.17"D)

                SELECT BAY (For 3«" Floppy Disk Drive or CD-ROM):
                     Maximum device size: 17 x 128.8 x 140.6mm
                                           (0.6"H x 3.78"W x 4.47"D)

WEIGHT: 18.0 lbs. NOTE: Monitor stand holds 77 lbs. maximum.
                                 Stand weight: 6 lbs.

PORTS: 1 - RS232C serial port   1 - SCSI-2 port
                    16550 UART equiv.   1 - Microphone (mini-jack)
                1 - ECP Parallel printer   1 - Headphone (mini-jack)
                    port   1 - Line-in (mini-jack)
                1 - analog VGA port, 15 pin   1 - Line-out (mini-jack)
                1 - PS/2 keyboard port   1 - Joystick/MIDI I/F
                1 - PS/2 mouse port

POWER: AC INPUT: Voltage: 100-240V   Frequency: 50-60Hz
                            Current: 2.0A (50Hz); 1.1 (60Hz)
                            Universal power supply (Auto-sensing)

                DC OUTPUT: Continuous voltage for operation: 15 volts
                            Continuous current for operation: 2.7A

                EXPANSION SLOTS and 5¬" EXPANSION BAY:

```
                    Volts DC    Continuous Amps    Peak Amps

                  + 3.3V              7.0
                  + 5V ñ5%            5.9              8.2
                  - 5V ñ10%           0.3               -
                  + 12V ñ5%           1.8              4.0
                  - 12V ñ10%          0.3               -
------------------------------------------------------------------------
----
SECURITY:      3 position key-lock (2 keys included)
               50 unique security keys
               Software security
               NoteWorthy lock slot
               Additional metal lever for added security
------------------------------------------------------------------------
----
FEATURES:      Front mounted Stereo Speakers  (28mm) with volume control
               Auto eject button
               Optimized for Windows 95 with Plug n' Play
               Hot Docking Support
               CRT Stand (holds 77 lbs. Maximum)
               Docking status LED indicator
               VCR style docking mechanism
```