

Satellite Pro™[Notebooks](#)[Home](#)[Main](#) - [Specifications](#) - [Accessories](#) - [Return to Index](#)**Satellite Pro - 430CDT****Processor**

- Intel Pentium® (2.9/3.3V), running at 120MHz
- 16KB write back cache in CPU
- Real time clock/calendar
- Math coprocessor integrated

Memory

- 16MB EDO RAM standard
- Expandable to 48MB RAM using a 8, 16 or 32MB user installable EDO memory

Disk Drives**Hard Disk Drive**

- 1.35 billion byte (=1.26GB)
- 13 msec. average access time

CD-ROM Drive

- Internal 10x average speed EIDE CD-ROM Drive
- Applicable Disc: Red Book, Yellow Book, CD-ROM XA, CD-Bridge, Photo-CD, Video CD, CD-I, CD-G, and CD Plus
- Average Sustained Data Transfer Rate:

Yellow Book Mode 1

- 150 KB/sec (1x)
- 600 KB/sec (4x)

Expansion

- PC Card (PCMCIA) slot(s):
 - 2 Type II slots (5mm) or 1 Type III slot (10.5mm)
 - Supports PC Cards, and Zoomed Video PC Cards
- Dedicated Toshiba memory expansion slot
- Optional Enhanced Port Replicator with 2 separate Type III PC Card slots

Standard Interfaces

- Super VGA monitor port
- High speed 9-pin RS-232-C serial port
- High performance 25-pin parallel port (ECP)
- PS/2 keyboard/mouse port
- 176-pin bus connector for optional Enhanced Port Replicator
- External microphone, line-in, and stereo headphone ports (1/8")
- IrDA 1.0 (115Kbps) compliant serial infrared ports

Software

- 1500 KB/sec (10x)

Yellow Book Mode 2

- 171 KB/sec (1x)
- 684 KB/sec (4x)
- 1700 KB/sec (10x)
- Burst (ATAPI): 11.1 MB/sec (PIO mode 3)
- Average access time: 180ms (10x)
- Buffer size: 128KB

Floppy Disk Drive

- 1.44MB, 3.5" floppy diskette drive included (user-swappable with CD-ROM drive)

Display System

- IBM Super Video Graphics Array (SVGA) compatible display system
- 2MB Video RAM
- TFT Active Matrix colour display
- 16.7 million colours at 800x600 with Windows[®] display driver
- Simultaneous display on external monitor at 800x600 up to 16.7 million colours
- 11.3" diagonal
- Local bus video
- Port for external "Super VGA" display
- 640x480x16.7 million
- 800x600x16.7 million
- 1,024x768x65,536

- Dual install of Toshiba MS-DOS 6.22 operating system, MS-Windows[®] for Workgroups 3.11, and other utilities OR Windows[®] 95 and Toshiba utilities pre-installed
- User has one time option to choose the operating system at the first boot-up

Limited Warranty

- Canada & International limited warranty
- Three years parts and labour

Dimensions and Weight

- 11.8" (W) x 9.3" (D) x 2.2" (H)
- 299mm (W) x 235mm (D) x 57mm (H)
- 7.0 lbs (3.2kg) with battery, internal floppy disk drive and built-in AC adaptor
- 7.5 lbs (3.4kg) with battery, internal CD-ROM drive and built-in AC adaptor

MaxTime™ Power System

- Removable, rechargeable Lithium Ion (Lilon) battery pack
- 2 to 4 hours battery life with normal usage
- Recharges in 2-3 hours when system is off / 5-8 hours when system is on
- Low battery warning light / audible alarm
- Display panel close suspend / open resume
- Alarm power on

- 1,280x1,024x256
- Virtual display allows up to 1,280x1,024 viewable area on 800x600 internal display

Special Features

- User swappable 10X average speed CD-ROM drive via SelectBay™
- Floppy disk drive is user swappable in SelectBay™ with CD-ROM and can be used externally
- System Control HotKeys
- Built-in Universal AC adaptor
- AccuPoint™ Pointing Stick
- Flash BIOS
- Plug-and-Play 1.0a BIOS
- APM 1.2 in BIOS
- VESA support in video BIOS
- Built-in Sound System:
 - Provides high quality 16-bit, 44.1KHz WAV audio for annotation and recording .WAV files, plus playback of MIDI files
 - Volume control dial
- IrDA 1.0 (115Kbps) compliant serial fast infrared port

- Automatic display and hard drive shut down after user specified time of keyboard inactivity
- Automatic CPU "sleep" mode to enhance battery life
- AutoResume electronic bookmark

Keyboard

- 82-key sculptured keyboard (101-key keyboard compatible)
- 12 dedicated function keys
- 8 dedicated cursor control keys; arrow keys arranged in easy-to-use inverted "T" pattern
- Integrated numeric keypad
- Supports optional external PS/2 style 101-key enhanced keyboard

Standard Features

- Universal AC adapter (100-240VAC, 50-60Hz input, 15VDC, 2.0A, 30W output)
- System reset button

Security

- Power on password
- Kensington cable lock slot (cable optional)

Suggested List Price

- 430CDT with 1.26GB hard disk drive and TFT active matrix colour display - **\$ 3,609**



Design and specification subject to change without notice.

MS-DOS and Windows are registered trademarks of Microsoft Corporation. MMX is a trademark of Intel Corporation. Pentium is a registered trademark of Intel Corporation. PS/2 is a registered trademark of International Business Machines.

All other brand and product names are trademark
of their respective companies.

[Back to top](#)

[Toshiba of Canada Limited](#)

[Home](#) 